



Contact us 800-892-3755

CustServ@jeffersonelectric.com

www.JeffersonElectric.com

## SWITCH INQUIRY FORM

Items marked by " \* " are necessary.

### Customer Information\*

Today's Date

First Name

Last Name

E-Mail

Phone

Company

City/State/Province

Quote Due Date

### Switch Preference\*

No Preference	Powercon
Schneider	Siemens
ABB	Eaton

### Switch Orientation\*

Left Side	Right Side
-----------	------------

### Switch Size\*

5KV, 600A 3Ø,3W, 60KV BIL, 40kAIC  
 15KV, 600A 3Ø,3W, 95KV BIL, 40kAIC  
 5KV, 1200A 3Ø,3W, 60KV BIL, 40kAIC  
 15KV, 1200A 3Ø,3W, 95KV BIL, 40kAIC

### Enclosure\*

NEMA 1	NEMA 3R
--------	---------

Options

4" Diameter Infra-Red Window  
 Kirk Key Interlocks  
 (Note: specify Kirk Key on transformer also)

### Arrestors

Lightning Arrestors (Set of 3)

Distribution Class  
 Intermediate Class  
 Station Class  
 None

### Transformer Information\*

kVA  
 Primary Voltage  
 Secondary Voltage

### Fusing\*

Yes	No
-----	----

Fuse selection based on the transformer.

Rule of thumb: 1.33 X the self-cooled full load of the transformer.

Current Limiting CLE Fuses (5.5KV with Fuse Clips, Set of 3)

20E	25E	30E	40E
50E	65E	80E	100E
125E	150E	175E	200E
250E	300E	350E	400E
450E			

Current Limiting CLE Fuses (15.5KV with Fuse Clips, Set of 3)

• Indicates Double Barrel Fuses

20E	25E	30E	40E
50E	65E	80E	100E
125E•	150E•	175E•	200E•
250E•	300E•		

### Options

Fuse Clips (Set of 3)  
 Double Barrel Fuse Clips (Set of 3)  
 Blown Fuse Indicator Light  
 Spare Fuse Pocket

### Other Options:

Thermostat	Insulated Bus
Strip Heater	Indicator Lights
Light	Auxiliary Switch
Ammeter	Voltmeter
Porcelain Insulator	
Ground Ball Stud with Cover	
Current Transformer	
Potential Transformer	
Control Transformer	

### Notes/Special Requirements

#### FOR OFFICE USE ONLY

Part No \_\_\_\_\_ Quote No \_\_\_\_\_  
 Quoted By \_\_\_\_\_ Date \_\_\_\_\_